
sprockets.mixins.sentry

Release 1.2.0

Sep 18, 2018

Contents

1	Installation	3
2	Requirements	5
3	API Documentation	7
4	Examples	9
5	Version History	11
6	Issues	13
7	Source	15
8	License	17
	Python Module Index	19

A RequestHandler mixin for sending exceptions to Sentry

CHAPTER 1

Installation

`sprockets.mixins.sentry` is available on the [Python Package Index](#) and can be installed via `pip` or `easy_install`:

```
pip install sprockets.mixins.sentry
```


CHAPTER 2

Requirements

- raven
- tornado

`mixins.sentry`

A `RequestHandler` mixin for sending exceptions to Sentry

class `sprockets.mixins.sentry.SanitizeEmailsProcessor` (*client*)
Remove all email addresses from the payload sent to sentry.

class `sprockets.mixins.sentry.SentryMixin` (**args, **kwargs*)
Report unexpected exceptions to Sentry.

Mix this in over a `tornado.web.RequestHandler` to report unhandled exceptions to Sentry so that you can figure out what went wrong. In order to use this mix-in, all that you have to do is define the `SENTRY_DSN` environment variable that contains your projects Sentry DSN. Whenever a request comes in and the environment variable is set, this mix-in will create a new `raven.base.Client` instance and make it available via the `sentry_client` property.

If an exception is caught by `_handle_request_exception()`, then it will be reported to Sentry in all its glory.

sentry_client

The `raven.base.Client` instance or `None` if sentry reporting is disabled. You can modify attributes of the client as required for your application – for example, you can add new modules by adding to `self.sentry_client.include_paths`.

sentry_extra

A `dict` of extra information to pass to sentry when an exception is reported.

sentry_tags

A `dict` of tag and value pairs to associated with any reported exceptions.

`sprockets.mixins.sentry.get_client` (*application*)

Retrieve the sentry client for *application*.

Parameters *application* (`tornado.web.Application`) – application to retrieve the sentry client for.

Returns a `raven.base.Client` instance or `None`

Return type `raven.base.Client`

`sprockets.mixins.sentry.install(application, **kwargs)`

Call this to install a sentry client into a Tornado application.

Parameters

- **application** (`tornado.web.Application`) – the application to install the client into.
- **kwargs** – keyword parameters to pass to the `raven.base.Client` initializer.

Returns `True` if the client was installed by this call and `False` otherwise.

This function should be called to initialize the Sentry client for your application. It will be called automatically with the default parameters by `SentryMixin` if you do not call it during the creation of your application. You should install the client explicitly so that you can set at least the following properties:

- **include_paths** list of python modules to include in tracebacks. This function ensures that `raven`, `sprockets`, `sys`, and `tornado` are included but you probably want to include additional packages.
- **release** the version of the application that is running

See [the raven documentation](#) for additional information.

CHAPTER 4

Examples

The following application will report errors to sentry if you export the SENTRY_DSN environment variable and make a request to <http://localhost:8000/whatever> provided that *whatever* is not an integer.

```
import sys
import signal

from tornado import ioloop, web

from sprockets.mixins import sentry

class Handler(sentry.SentryMixin, web.RequestHandler):

    def initialize(self, **kwargs):
        tags = kwargs.pop('tags', dict())
        super(Handler, self).initialize(**kwargs)
        self.sentry_tags.update(tags)

    def get(self, status_code):
        self.set_status(int(status_code))

def make_application(app_tags):
    application = web.Application([web.url(r'/(\\S+)', Handler)])
    sentry.install(application, include_paths=[__name__], tags=app_tags)
    return application

def stop(signo, frame):
    iol = ioloop.IOLoop.current()
    iol.add_callback_from_signal(iol.stop)

if __name__ == '__main__':
```

(continues on next page)

(continued from previous page)

```
app_tags = {}
for arg in sys.argv[1:]:
    name, _, value = arg.partition('=')
    app_tags[name] = value

signal.signal(signal.SIGINT, stop)
app = make_application(app_tags)
app.listen(8000)
ioloop.IOLoop.current().start()
```

CHAPTER 5

Version History

- 1.2.0
 - Extend raven pin so that we can use python 3.7
 - Advertise python 3.7 support
 - Drop python 3.4 from support matrix
 - Remove unused import of `urllib.parse`
- 1.1.2
 - Add email sanitization processor
- 1.1.1
 - Fix password scrubbing in URLs.
 - Remove support for python 2.6, 3.2, and 3.3
- 1.1.0
 - Move raven client initialization into `sprockets.mixins.sentry.install`
 - Add support for setting `raven.Client` options when calling `install` on the application.
 - The sentry “environment” is set to the `$ENVIRONMENT` environment variable if it is set.
- 1.0.0
 - Work around [getsentry/raven-python#735](#)
- 0.4.0 (16-Dec-2015)
 - Ignore `web.Finish` exceptions
- 0.3.0 (13-Jul-2015)
 - Add `sprockets.mixins.sentry.SentryMixin.sentry_extra`
 - Add `sprockets.mixins.sentry.SentryMixin.sentry_tags`
 - Improve module reporting in Sentry messages

- Improved documentation
- 0.2.0 (22-Jun-2015)
 - Stop reporting `tornado.web.HTTPError`
- 0.1.0 (13-May-2015)
 - Initial public release

CHAPTER 6

Issues

Please report any issues to the Github project at <https://github.com/sprockets/sprockets.mixins.sentry/issues>

CHAPTER 7

Source

`sprockets.mixins.sentry` source is available on Github at <https://github.com/sprockets/sprockets.mixins.sentry>

CHAPTER 8

License

`sprockets.mixins.sentry` is released under the [3-Clause BSD license](#).

S

`sprockets.mixins.sentry`, [7](#)

E

environment variable
 SENTRY_DSN, 9

G

get_client() (in module sprockets.mixins.sentry), 7

I

install() (in module sprockets.mixins.sentry), 8

S

SanitizeEmailsProcessor (class in sprockets.mixins.sentry), 7

sentry_client (sprockets.mixins.sentry.SentryMixin attribute), 7

SENTRY_DSN, 9

sentry_extra (sprockets.mixins.sentry.SentryMixin attribute), 7

sentry_tags (sprockets.mixins.sentry.SentryMixin attribute), 7

SentryMixin (class in sprockets.mixins.sentry), 7

sprockets.mixins.sentry (module), 7